



TraiTel Account Management API

v1.0

Table of Contents

About the API:.....	3
Modes of operation:	5
Balance:.....	7
querybalance	7
Sub-Account Management:	8
querysubaccounts	8
addsubaccount.....	8
delsubaccount.....	10
updatesubaccount	11
DID Management:	12
querynumbers	12
assignnumber	13
querydidcountries	14
querydidcities	15
querydids	16
subscribedid	17
IVML Management:	18
listivr	18
listivml	19
addivml	20
updateivml	21
deleteivml	22
Fax Activity Log:.....	23
logfaxin	23
logfaxout.....	24
Voice Activity Log:.....	25
logvoicein.....	25
logvoiceout	26
SMS Activity Log:	26
logsmsin.....	28
logsmsout	30
Time-Zone Management:	31
settimezone	31
querytimezone.....	32
Service Item Cost Queries:.....	33
querysmcost.....	33
queryvoicecost.....	34
queryfaxcost	35
Faxing Error Codes	36
API Error Codes	38

About the API:

The TraiTel Account Management API allows you to query and alter account settings and logs. The API covers a wide range of operations, from retrieving messaging logs, to querying your account balance, to configuring Voice services, etc.

All requests are submitted to the following URL:

<http://api.traitel.com/accountmanager.pl>

An alternate URL is available should the primary API gateway fail to respond:

<http://api2.traitel.com/accountmanager.pl>

HTTPS is optional on both gateways.

Each API call requires at minimum, the following three parameters:

user	Your TraiTel username
pass	Your TraiTel password
mode	The desired action to perform. See below.

Each API call will respond with a standard HTTP header, followed by either an error message, or a positive indication and the queried information. All newlines in the body of HTTP responses are represented by the character: \n

All API errors will appear in the following manner:

Error 012: Human-Readable Error Message

All API successes will display on a single line:

Ok

followed by the query output.

There are two possible errors on a global scale:

Error 001: Service Unavailable.

Meaning: This API gateway cannot process your request at this time.

Error 002: Authentication failed.

Meaning: The provided credentials are invalid.

Modes of operation:

The third required parameter for any request to this API is the 'mode' parameter. The 'Mode' Parameter must be one of the following:

Balance:

querybalance Returns the current account credit balance

Sub-Account Management:

querysubaccounts Returns a list of sub-accounts
addsubaccount Adds a sub-account to the account
delsubaccount Deletes a sub-account from the account
updatesubaccount Updates information about a sub-account

DID Management:

querynumbers List available DID's registered to the account
assignnumber Assigns a DID to a specific service
querydidcountries Lists countries in which DID's are available for subscription
querydidcities Lists cities within a country in which DID's are available
querydids Offers a DID for registration
subscribedid Subscribes to a given DID

IVML Management:

listivr Lists IVR menus
listivml Lists IVML configurations
addivml Adds a new IVML configuration
updateivml Updates an existing IVML configuration
deleteivml Deletes an IVML configuration

Fax Activity Log:

logfaxin List inbound fax activity
logfaxout List outbound fax activity and costs

Voice Activity Log:

logvoicein List inbound voice activity and costs
logvoiceout List outbound voice activity and costs

SMS Activity Log:

logsmsin List SMS inbound activity
logsmsout List SMS outbound activity and costs

Time-Zone Management:

settimezone Set the account Time Zone
querytimezone View the account Time Zone

Service Item Cost Queries:

querysmscost Query the cost of an SMS to a specified number
queryvoicecost Query the cost of a call to a specific destination
queryfaxcost Query the cost of a fax to a specific destination

Balance:

querybalance

Retrieves the account's current available credit balance. The credit balance is returned without formatting or currency symbols, as a decimal value. The credit balance returned is accurate in real-time for single accounts; however, it is only updated on regular intervals for accounts with shared credit balances.

Parameters:

none

Errors:

none

Success:

Ok

credit_balance

Sub-Account Management:

querysubaccounts

Returns a list of sub-accounts registered to this account. The list returned is in CSV format.

Parameters:

none

Errors:

none

Success:

Ok

Sub-ID,Email,First Name,Last Name,Company,Fax Headline

CSV Data...

addsubaccount

Adds a sub-account to the account.

Parameters:

<i>alias</i>	Required	An alias for this sub-account.
<i>email</i>	Optional	An email address associated to this sub-account.
<i>firstname</i>	Optional	The first name of the owner of this sub-account.
<i>lastname</i>	Optional	The last name of the owner of this sub-account.
<i>company</i>	Optional	The organisation of the owner of this sub-account.
<i>faxheadline</i>	Optional	For outbound faxing, the fax headline displayed.

Errors:

Error 101: Email address already registered elsewhere.

Occurs if the email address provided is registered to another sub-account or account.

Error 102: Alias already registered.

Occurs if the alias given already exists on another sub-account.

Error 104: Invalid email address.

Occurs if the provided email address is invalid.

Error 200: Incomplete request.

Occurs if a required parameter is missing or a parameter is invalid.

Success:

Ok

subAccountID

Returns the Sub-Account ID of the newly created sub-account.

delsubaccount

Deletes a sub-account. This action cannot be undone. DID's associated with a sub-account are returned to the main account as unassigned numbers.

Parameters:

subid required The sub-account ID to delete

Errors:

Error 105: Invalid sub-account ID.

Occurs when the given Sub-Account ID is invalid.

Error 200: Incomplete request.

Occurs if a required parameter is missing or a parameter is invalid.

Success:

Ok

updatesubaccount

Updates information about a sub-account. All parameters but the sub-account ID are optional. Parameters not specified will retain their existing value. Only supplied parameters will overwrite existing account settings.

Parameters:

<i>subid</i>	Required	The sub-account ID to update
<i>email</i>	Optional	An email address associated to this sub-account.
<i>alias</i>	Optional	An alias for this sub-account.
<i>firstname</i>	Optional	The first name of the owner of this sub-account.
<i>lastname</i>	Optional	The last name of the owner of this sub-account.
<i>company</i>	Optional	The organization of the owner of this sub-account.
<i>faxheadline</i>	Optional	For outbound faxing, the fax headline displayed.

Errors:

Error 101: Email address already registered elsewhere.

Occurs if the email address provided is registered to another sub-account or account.

Error 102: Alias already registered.

Occurs if the alias given already exists on another sub-account.

Error 104: Invalid email address.

Occurs if the provided email address is invalid.

Error 105: Invalid sub-account ID.

Occurs if the requested sub-account does not exist.

Error 200: Incomplete request.

Occurs if a required parameter is missing or a parameter is invalid.

Success:

Ok

DID Management:

querynumbers

Lists all available DIDs registered to the account. The list may be filtered by service if requested. The list indicates any assignment the DID might presently occupy.

Parameters:

<i>subid</i>	Optional	Filters the list by the given sub-account ID
<i>service</i>	Optional	fax: Lists faxing DIDs voice: Lists voice DIDs sms: Lists SMS DIDs

Errors:

Error 105: Invalid sub-account ID.

Occurs when an invalid sub-account ID is given.

Error 200: Incomplete request.

Occurs if a required parameter is missing or a parameter is invalid.

Success:

Ok

Number,Service,Assigned-Service,Assigned-ID

CSV Data...

Service: fax, voice, sms

Assigned-Service: IVR: Assigned-ID represents the IVR ID #

IVML: Assigned-ID represents the IVML ID #

SIP: Assigned-ID represents the Sub-Account, if any

assignnumber

Assigns a DID to a specific service.

Parameters:

<i>number</i>	Required	The DID to be assigned
<i>service</i>	Required	The destination service: fax, voice
<i>servicetype</i>	Required	For voice only, specify IVR, IVML, or SIP
<i>serviceid</i>	Required	For IVR, specify IVR menu ID # For IVML, specify IVML configuration ID # For SIP, specify 0, or a Sub-Account ID

Errors:

Error 105: Invalid sub-account ID.

Occurs when SIP is selected but an invalid Sub-Account ID was provided as *serviceid*.

Error 107: Invalid service.

Occurs when the service specified is invalid

Error 108: Service not available.

Occurs when the selected service is not available for the given DID

Error 109: Invalid IVR ID.

Occurs when IVR is selected but the given *serviceid* does not match an IVR ID

Error 110: Invalid IVML ID.

Occurs when IVML is selected but the given *serviceid* does not match an IVML ID

Error 113: Invalid DID.

Occurs when the specified number does not exist or does not belong to the account.

Error 200: Incomplete request.

Occurs if a required parameter is missing or a parameter is invalid.

Success:

Ok

querydidcountries

Lists countries in which DIDs are available for subscription. This request shall be used to automate the subscription of new DID's. Note that monthly charges may apply.

Parameters:

service Required One of: fax,voice,.sms

Errors:

Error 107: Invalid service.

Occurs when the service parameter is invalid.

Error 200: Incomplete request.

Occurs if a required parameter is missing or a parameter is invalid.

Success:

Ok

CountryName

CSV Data...

querydidcities

Lists cities within a country in which DIDs are available. Should be used only after issuing a 'querydidcountries' request. Note that monthly charges may apply for the subscription of DIDs.

Parameters:

service Required One of: fax, voice, sms
country Required A Country Name received by “querydidcountries”

Errors:

Error 107: Invalid service.

Occurs when the service parameter is invalid.

Error 111: Invalid country.

Occurs when the given country is not valid or not available.

Error 200: Incomplete request.

Occurs if a required parameter is missing or a parameter is invalid.

Success:

Ok

CountryName,CityName

CSV Data...

querydids

Offers one or more DID for registration. Note that DIDs are not registered at this point. They are merely listed as available DIDs for registration. Registering DIDs may incur monthly charges. This query should only be called after successfully calling 'querydidcountries' and 'querydidcities'.

Parameters:

<i>service</i>	Required	One of: fax, voice, sms
<i>country</i>	Required	A Country Name received by “querydidcountries”
<i>city</i>	Required	A City Name received by “querydidcities”
<i>quantity</i>	Optional	The amount of DIDs to retrieve. Default 1, Maximum 10

Errors:

Error 107: Invalid service.

Occurs when the service parameter is invalid.

Error 111: Invalid country.

Occurs when the given country is not valid or not available.

Error 112: Invalid city.

Occurs when the given city name is invalid.

Error 200: Incomplete request.

Occurs if a required parameter is missing or a parameter is invalid.

Success:

Ok

CountryName, CityName, DID

CSV Data...

subscribedid

Subscribes to a given DID. Upon successful completion, this subscription may incur monthly charges to your account.

Parameters:

<i>service</i>	Required	One of: fax, voice, sms
<i>country</i>	Required	A Country Name received by “querydidcountries”
<i>city</i>	Required	A City Name received by “querydidcities”
<i>did</i>	Required	A DID received by “querydids”

Errors:

Error 107: Invalid service

Occurs when the service parameter is invalid.

Error 111: Invalid country.

Occurs when the given country is not valid or not available.

Error 112: Invalid city.

Occurs when the given city name is invalid.

Error 113: Invalid DID.

Occurs when the given DID is invalid

Error 114: DID not available.

Occurs when the given DID is not available.

Error 200: Incomplete request.

Occurs if a required parameter is missing or a parameter is invalid.

Success:

Ok

IVML Management:

listivr

Provides a list of current IVR menus. The results may be used to identify IVR ID #'s for DID assignment.

Parameters:

none

Errors:

none

Success:

Ok

ID,Name,DIDs

CSV Data...

The *DIDs* column will contain a space-delimited list of numbers assigned to the given IVR menu. The *DIDs* column will list 'outbound' for IVR Outbound service.

listivml

Lists IVML configurations. IVML Configurations can be created, modified, deleted, and assigned via this API, or via WebMessaging.

Parameters:

none

Errors:

none

Success:

Ok

ID,Name,LaunchURL,ResultURL,DIDs

CSV Data...

The *DIDs* column will contain a space-delimited list of numbers assigned to the given IVML Configuration. The *DIDs* column will list 'outbound' for IVML Outbound service.

addivml

Creates a new IVML configuration.

Parameters:

<i>name</i>	Required	A reference name for the IVML configuration
<i>launchurl</i>	Required	A URL from which IVML instructions will be fetched receiving an inbound call or placing an outbound call.
<i>resulturl</i>	Optional	A URL to which the IVML call result is delivered.
<i>type</i>	Required	One of the following: inbound, outbound

Errors:

Error 115: No subscription to IVR.

Occurs when the account is not registered to receive the IVML / IVR service.

Error 116: Duplicate name.

Occurs if an IVML configuration already exists by the given name.

Error 200: Incomplete request.

Occurs if a required parameter is missing or a parameter is invalid.

Success:

Ok

IVML-ID#

updateivml

Updates an existing IVML configuration

Parameters:

<i>ivmlid</i>	Required	An existing IVML Configuration ID #
<i>name</i>	Optional	A reference name for the IVML configuration
<i>launchurl</i>	Optional	A URL from which IVML instructions will be fetched receiving an inbound call or placing an outbound call.
<i>resulturl</i>	Optional	A URL to which the IVML call result is delivered.
<i>type</i>	Optional	One of the following: inbound, outbound

Errors:

Error 110: Invalid IVML ID.

Occurs when the given IVML ID # does not exist.

Error 115: No subscription to IVR.

Occurs when the account is not registered to receive the IVML / IVR service.

Error 116: Duplicate name

Occurs if an IVML configuration already exists by the given name.

Error 200: Incomplete request.

Occurs if a required parameter is missing or a parameter is invalid.

Success:

Ok

deleteivml

Deletes an IVML configuration. This action cannot be undone. Any assigned DID will be returned to the main account as an unassigned DID.

Parameters:

ivmlid Required The IVML Configuration ID # to delete

Errors:

Error 110: Invalid IVML ID.

Occurs when the provided IMVL Configuration ID # does not exist.

Error 200: Incomplete request.

Occurs if a required parameter is missing or a parameter is invalid.

Success:

Ok

Fax Activity Log:

logfaxin

List inbound fax activity. Returns a CSV containing the inbound fax log for the given period and (optionally) sub-account.

Parameters:

<i>startdate</i>	Required	The starting date of the returned log. Format must be: yyyy-mm-dd
<i>enddate</i>	Required	The ending date of the returned log, inclusive.
<i>limit</i>	Optional	The maximum number of records to return
<i>subid</i>	Optional	Filters the log to a given sub-account ID.

Errors:

Error 105: Invalid sub-account ID.

Occurs when the provided Sub-Account ID does not exist

Error 117: Invalid end date.

Occurs if the date format is invalid, the date is invalid, or the date is in the future.

Error 118: Invalid start date.

Occurs if the date format is invalid, the date is invalid, or the date is in the future.

Error 200: Incomplete request.

Occurs if a required parameter is missing or a parameter is invalid.

Success:

Ok

ID,Sub-ID,Date,Time,From,To,FaxStationID,Pages,Speed,Duration

CSV Data...

logfaxout

List outbound fax activity and costs. Returns a CSV of the log for the given period.

Parameters:

<i>startdate</i>	Required	The starting date of the returned log. Format must be: yyyy-mm-dd
<i>enddate</i>	Required	The ending date of the returned log, inclusive.
<i>limit</i>	Optional	The maximum number of records to return
<i>subid</i>	Optional	Filters the log to a given sub-account ID.

Errors:

Error 105: Invalid sub-account ID.

Occurs when the provided Sub-Account ID does not exist

Error 117: Invalid end date.

Occurs if the date format is invalid, the date is invalid, or the date is in the future.

Error 118: Invalid start date.

Occurs if the date format is invalid, the date is invalid, or the date is in the future.

Success:

Ok

ID,Sub-ID,Date,Time,From,To,Pages,Speed,Duration,Cost,Attempt,ErrorCode
CSV Data...

The Cost value is pre-tax.

The ErrorCode value is 0 on success, or otherwise a positive value indicating a faxing error. The possible errors are listed in the Faxing Error Codes table appended to this document.

Voice Activity Log:

logvoicein

List inbound voice activity and costs. Returns a CSV of the log for the given period.

Parameters:

<i>startdate</i>	Required	The starting date of the returned log. Format must be: yyyy-mm-dd
<i>enddate</i>	Required	The ending date of the returned log, inclusive.
<i>limit</i>	Optional	The maximum number of records to return
<i>subid</i>	Optional	Filters the log to a given sub-account ID.

Errors:

Error 105: Invalid sub-account ID.

Occurs when the provided Sub-Account ID does not exist

Error 117: Invalid end date.

Occurs if the date format is invalid, the date is invalid, or the date is in the future.

Error 118: Invalid start date.

Occurs if the date format is invalid, the date is invalid, or the date is in the future.

Success:

Ok

ID,Sub-ID,Date,Time,From,To,Duration,Result,Cost,IVMLID

CSV Data...

The Cost value is pre-tax.

The Result column will contain one of the following: answered, failed.

The Duration field represents the call duration in seconds. On a failed call, this value represents the duration of the call from initiation until failure. On a successful call, this value represents the time from the time the call was answered, to the end of the call.

logvoiceout

List outbound voice activity and costs. Returns a CSV of the log for the given period.

Parameters:

<i>startdate</i>	Required	The starting date of the returned log. Format must be: yyyy-mm-dd
<i>enddate</i>	Required	The ending date of the returned log, inclusive.
<i>limit</i>	Optional	The maximum number of records to return
<i>subid</i>	Optional	Filters the log to a given sub-account ID.

Errors:

Error 105: Invalid sub-account ID.

Occurs when the provided Sub-Account ID does not exist

Error 117: Invalid end date.

Occurs if the date format is invalid, the date is invalid, or the date is in the future.

Error 118: Invalid start date.

Occurs if the date format is invalid, the date is invalid, or the date is in the future.

Success:

Ok

ID,Sub-ID,Date,Time,From,To,Duration,Result,Cost,IVMLID

CSV Data...

The Cost value is pre-tax.

The Result column will contain one of the following: answered, failed.

The Duration field represents the call duration in seconds. On a failed call, this value represents the duration of the call from initiation until failure. On a successful call, this value represents the time from the time the call was answered, to the end of the call.

SMS Activity Log:

logsmsin

Returns a CSV of inbound SMS traffic within the provided date range.

Parameters:

<i>startdate</i>	Required	The starting date of the returned log. Format must be: yyyy-mm-dd
<i>enddate</i>	Required	The ending date of the returned log, inclusive.
<i>limit</i>	Optional	The maximum number of records to return
<i>subid</i>	Optional	Filters the log to a given sub-account ID.

Errors:

Error 105: Invalid sub-account ID.

Occurs when the provided Sub-Account ID does not exist

Error 117: Invalid end date.

Occurs if the date format is invalid, the date is invalid, or the date is in the future.

Error 118: Invalid start date.

Occurs if the date format is invalid, the date is invalid, or the date is in the future.

Error 200: Incomplete request.

Occurs if a required parameter is missing or a parameter is invalid.

Success:

Ok

ID,Sub-ID,Date,Time,From,To,MessageType,Message

CSV Data...

MessageType values:

ASCII: The given Message is an ASCII Message. New Line characters are escaped with \

U16: The given Message is a hexadecimal string represented a Unicode-16bit encoded message.

logsmsout

Returns a CSV of outbound SMS traffic within the provided date range.

Parameters:

<i>startdate</i>	Required	The starting date of the returned log. Format must be: yyyy-mm-dd
<i>enddate</i>	Required	The ending date of the returned log, inclusive.
<i>limit</i>	Optional	The maximum number of records to return
<i>subid</i>	Optional	Filters the log to a given sub-account ID.

Errors:

Error 105: Invalid sub-account ID.

Occurs when the provided Sub-Account ID does not exist

Error 117: Invalid end date.

Occurs if the date format is invalid, the date is invalid, or the date is in the future.

Error 118: Invalid start date.

Occurs if the date format is invalid, the date is invalid, or the date is in the future.

Error 200: Incomplete request.

Occurs if a required parameter is missing or a parameter is invalid.

Success:

Ok

ID,Sub-ID,Date,Time,From,To,Sent,Tracking,Cost

CSV Data

The "Cost" value is pre-tax.

Time-Zone Management:

settimezone

Sets the account timezone to the given value. Time Zone names are retrieved from the IANA Time Zone Database. Submitted Time Zones must match a valid IANA Time Zone name.

Parameters:

<i>tz</i>	Required	Name of the time-zone
-----------	----------	-----------------------

Errors:

Error 119: Invalid timezone.

Occurs if the given time zone name is not found in TraiTel's database.

Error 200: Incomplete request.

Occurs if a required parameter is missing or a parameter is invalid.

Success:

Ok

time_zone_name

querytimezone

Retrieves the account timezone. Time Zone names are retrieved from the IANA Time Zone Database.

Parameters:

none

Errors:

none

Success:

Ok

time_zone_name

Service Item Cost Queries:

querysmcost

Queries the cost of an SMS to a specified recipient number. This function provides a means to retrieve an estimated cost of delivery for an SMS to a specified destination number.

Parameters:

<i>number</i>	Required	The mobile destination number, in international format.
<i>type</i>	Required	replies: returns the cost of the SMS delivery using an automatically assigned Sender-ID
<i>masking</i> :		returns the cost of the SMS delivery using a supplied Sender-ID or Alphanumeric Sender-ID
<i>tracking</i> :		returns the cost of the SMS delivery including Delivery Tracking results, using an automatically assigned Sender-ID
<i>masktrack</i> :		returns the cost of the SMS delivery including Delivery Tracking results, and a user-supplied Sender-ID or Alphanumeric Sender-ID

Errors:

Error 120: Invalid destination number.

Occurs when the provided destination number is unroutable or invalid.

Error 200: Incomplete request.

Occurs if a required parameter is missing or a parameter is invalid.

Success:

Ok

item_cost

The *item_cost* is returned as a decimal value, pre-tax, without currency symbol.

queryvoicecost

Queries the cost of a voice call to a specified recipient number. This function provides an estimated cost for the termination of a voice call to a given destination.

Parameters:

number Required The voice destination number, in international format.

Errors:

Error 120: Invalid destination number.

Occurs when the provided destination number is unroutable or invalid.

Error 200: Incomplete request.

Occurs if a required parameter is missing or a parameter is invalid.

Success:

Ok

FlagFall,PerSecond,PerMinute,BillingType,Cost

CSV Data

The result is returned in a CSV format where a single row under the header row indicates the cost breakdown for each call component. The *BillingType* column will list either “PerSecond” or “PerMinute” depending on how the call will be charged. The *Cost* is returned as a decimal value, pre-tax, without currency symbol.

queryfaxcost

Queries the cost of a fax delivery to a specified recipient number. This function gives an estimated cost for the delivery of a fax document to a given destination. Note that some delivery discounts or promotional offers activated in your account may result in invalid results being returned here.

Parameters:

number Required The fax destination number, in international format.

Errors:

Error 120: Invalid destination number.

Occurs when the provided destination number is unroutable or invalid.

Error 200: Incomplete request.

Occurs if a required parameter is missing or a parameter is invalid.

Success:

Ok

FlagFall,PerSecond,PerMinute,PerPage,BillingType,Cost

CSV Data

The result is returned in a CSV format where a single row under the header row indicates the cost breakdown for each call component. The *BillingType* column will list either “PerSecond”, “PerMinute”, “PerPage” or “Mixed” depending on how the call will be charged. The *Cost* is returned as a decimal value, pre-tax, without currency symbol.

Faxing Error Codes

The faxing error code is a three digit code. The first digit of the code represents the state of the faxing call, while the other two digits represent the faxing error.

State Code State Description

000	The fax was aborted before initialisation.
100	Call establishment preparation: The number has not been dialled.
200	Call establishment: The number has been dialled.
300	Call answered: The call has been answered.
400	Call voice channel: The call is answered and in a voice channel
500	Fax negotiation preparation: The call is ready to begin fax negotiation
600	Fax call: The fax is in progress.

Faxing Error Codes:

Code	Error	Description
00	General Error	An unknown error occurred
01	Line Error	An unspecified line error occurred.
02	Destination Busy	The destination returned a busy signal.
03	Destination Rejected	The call was remotely rejected.
04	No Answer	The call was not answered.
05	No Answer	The call was not answered.
06	Unknown Number	The destination number is invalid.
07	Invalid Number	The destination number is invalid.
08	Number Changed	The destination number no longer exists.
09	No Channel	There is no available line for this fax.
10	Line Error	An unspecified line error occurred.
11	No Channel	There is no available line for this fax.
12	Unspecified Error	An unspecified error occurred.

13 Unallocated Number The number dialled is not allocated.

Faxing Error Codes:

Code	Error	Description
14	Transferred	The call was transferred to another application.
15	Data Channel Failed	The fax data channel could not be established
16	No faxing device	There was no fax device at the destination.
17	Fax Training Failed	There was a failure establishing the fax channel.
18	Fax aborted remotely	The destination aborted the fax transmission. Possible causes are: out of paper, poor line quality, etc.
19	Fax aborted locally	The fax was aborted locally. This is normally due to a noisy or poor quality connection.
23	Incompatible Destination	The destination could not accept a voice or fax call.
27	Timed out	The fax transmission timed out.
99	Insufficient Funds/	Indicates the fax was cancelled by user request. Fax Cancelled

API Error Codes

The following table lists all errors returned by this API:

Global Errors:

Error 001: Service Unavailable.

Occurs when the API gateway is temporarily unable to process the request.

Error 002: Authentication failed.

Occurs when an invalid username or password is provided, or when an account is locked or disabled.

Request Errors:

Error 101: Email address already registered elsewhere.

Occurs when a sub-account registration or modification is rejected due a matching email address already assigned on another sub-account or within another account entirely.

Error 102: Alias already registered.

Occurs when a sub-account registration or modification is rejected due to a matching alias assigned to another sub-account.

Error 104: Invalid email address.

Occurs when a provided email address is technically invalid.

Error 105: Invalid sub-account ID.

Occurs when a provided sub-account ID does not exist.

Error 107: Invalid service.

Occurs when the specified service-type is invalid or does not exist.

Error 108: Service not available.

Occurs when the specified service-type is not available for the given DID.

Error 109: Invalid IVR ID.

Occurs when a provided IVR ID does not exist.

Error 110: Invalid IVML ID.

Occurs when a provided IVML Configuration ID does not exist.

Error 111: Invalid country.

Occurs when a provided country name does not exist or, does not match any existing country within our database or, does not match any country where a given service is queried.

Error 112: Invalid city.

Occurs when a provided city name does not exist when registering a DID.

Error 113: Invalid DID.

Occurs when a provided DID does not exist or is not formatted properly.

Error 114: DID not available.

Occurs when a DID registration fails due to a provided DID number becoming unavailable for registration.

Error 115: No subscription to IVR.

Occurs when an IVR or IVML operation is attempted on an account where the IVR service is not subscribed.

Error 116: Duplicate name.

Occurs when an IVML Configuration is created using a name already assigned to another IVML Configuration within the same account.

Error 117: Invalid end date.

Occurs when a provided date is not formatted properly or is in the future.

Error 118: Invalid start date.

Occurs when a provided date is not formatted properly or is in the future.

Error 119: Invalid timezone.

Occurs when a provided time-zone name is not valid or not within our database of time-zones.

Error 120: Invalid destination number.

Occurs when a destination number is provided for a service cost query, where the given number is either invalid, not formatted properly, or not routable by the given service.

Error 200: Incomplete request.

Occurs when any required field is not provided, or when a field value is

provided outside of the options offered for that field.